



Network PBU
Ethernet Magnetics
Selector Guide

About Our Ethernet Magnetics

100Base-TX | 1000Base-T | 2.5GBase-T | 5GBase-T | 10GBase-T



Pulse's Ethernet transformers are RoHS compliant and qualified at major PHY suppliers. 100/1000/2.5G/5G/10GBASE-T

Ethernet transformer modules are optimized for all major LAN transceivers. All modules provide electrical circuit isolation that meets IEEE 802.3, while maintaining signal integrity needed for the most demanding applications.

Features & Benefits

- ⚡ IEEE 802.3 Compliant to 10G
- ⚡ High Isolation up to 6kV
- ⚡ Higher Reliability (Carrier Class & AEC-Q200)
- ⚡ Single, Dual, Quad Packages, SMT, THR & BGA Options
- ⚡ Extended Temperature -40°C to +85°C
- ⚡ 2P/4P PoE/PoE+PoE++ Capable up to 140W max.

100Base-TX								
MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	PoE RATING
H0013NL	SINGLE	PCMCIA	1.98max	12.70	9.65	100BASE-TX	0 TO 70	NON-PoE
H0022NL	SINGLE	PCMCIA	2.16max	11.81	11.43	100BASE-TX	0 TO 70	NON-PoE
H0068ANL	SINGLE	PCMCIA	2.08	12.70	9.65	100BASE-TX	0 TO 70	NON-PoE
H1102NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	0 TO 70	NON-PoE
H1112NL*	SINGLE	SMT	4.88	14.81	14.73	100BASE-TX	0 TO 70	NON-PoE
H1164NL*	QUAD	SMT	5.84	28.58	16.00	100BASE-TX	0 TO 70	NON-PoE
H1174NL	DUAL	SMT	3.69	13.08	15.00	100BASE-TX	0 TO 70	NON-PoE
H1197NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	0 TO 70	NON-PoE
H1260NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	0 TO 70	NON-PoE
H1270NL	DUAL	SMT	3.68	13.08	14.99	100BASE-TX	0 TO 70	NON-PoE
H1302NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	0 TO 70	NON-PoE
H2006ANL*	DUAL	SMT	6.22	13.64	14.99	100BASE-TX	0 TO 70	PoE 15W
H2009NL*	DUAL	SMT	6.12	13.16	18.67	100BASE-TX	0 TO 70	PoE 15W
H2017NL	QUAD	SMT	7.24	28.45	16.00	100BASE-TX	0 TO 70	PoE 15W
H2019NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	0 TO 70	PoE 15W
HX0068ANL	SINGLE	PCMCIA	2.08	12.70	9.65	100BASE-TX	-40 TO +85	NON-PoE
HX1098NL	SINGLE	SMT	4.01	12.70	9.65	100BASE-TX	-40 TO +85	PoE 15W
HX1112QNL	SINGLE	SMT	4.88	14.73	14.73	100BASE-TX	-40 TO +85	NON-PoE
HX1148NL*	SINGLE	SMT	5.84	25.45	12.70	100BASE-TX	-40 TO +85	NON-PoE
HX1188NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	-40 TO +85	NON-PoE
HX1198NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	-40 TO +85	NON-PoE
HX1217NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	-40 TO +85	NON-PoE
HX1234NL*	QUAD	SMT	5.84	28.58	16.00	100BASE-TX	-40 TO +85	NON-PoE
HX1260NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	-40 TO +85	NON-PoE
HX1294NL	DUAL	SMT	5.87	13.67	18.87	100BASE-TX	-40 TO +85	NON-PoE
HX1305NL	DUAL	SMT	6.12	13.16	18.67	100BASE-TX	-40 TO +85	NON-PoE
HX1344NL	QUAD	SMT	5.72	28.45	16.00	100BASE-TX	-40 TO +85	NON-PoE
HX2019NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	-40 TO +85	PoE 15W
HX2260NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	-40 TO +85	PoE 15W
HX2305NL	DUAL	SMT	6.12	13.16	18.67	100BASE-TX	-40 TO +85	PoE 15W
HX2326NL	SINGLE	SMT	5.97	12.70	9.40	100BASE-TX	-40 TO +85	PoE+ 30W

* denotes parts require special dry pack handling as MSL is greater than 3

About Our Ethernet Magnetics

100Base-TX | 1000Base-T | 2.5GBase-T | 5GBase-T | 10GBase-T

100Base-TX - HIGH ISOLATION

MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	HI-POT RATING
HX1224CNL	SINGLE	SMT	6.22max	13.64	14.99	100BASE-TX	-40 TO +85	4KV * REINFORCED
H1262CNL	SINGLE	SMT	9.65max	12.70	9.65	100BASE-TX	-40 TO +85	3KVrms
HX1332NL	SINGLE	SMT	10.55max	25.40	17.20	100BASE-TX	-40 TO +85	4KV - 2PPP
HX1332CNL	SINGLE	SMT	10.55max	25.40	17.20	100BASE-TX	-40 TO +85	6KV - 2PPP
HX1333NL	SINGLE	SMT	8.65max	17.10	14.75	100BASE-TX	-40 TO +85	4.5KVrms
HX1339NL	SINGLE	SMT	7.87max	15.24	15.24	100BASE-TX	-40 TO +85	4.5KV * SUPPLEMENTARY

1000Base-TX

MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	PoE RATING
H5004ENL	SINGLE	SMT	5.72	17.53	16.00	1000BASE-T	0 TO 70	NON-PoE
H5007ENL	SINGLE	SMT	5.72	17.53	16.00	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5008NL	SINGLE	SMT	5.87	13.67	18.87	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5014NL	DUAL	SMT	7.24	27.81	15.37	1000BASE-T	0 TO 70	NON-PoE
H5015NL	SINGLE	SMT	4.57	17.65	15.75	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5020NL	DUAL	SMT	8.33	27.94	10.92	1000BASE-T	0 TO 70	NON-PoE
H5062NL	SINGLE	SMT	5.72	17.53	16.00	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5077NL	SINGLE	SMT	4.83	14.22	12.95	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5079NL	SINGLE	PCMCIA	2.54	19.94	14.73	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5084NL	SINGLE	SMT	4.00	15.24	10.29	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5120NL	SINGLE	PCMCIA	2.08	16.51	9.65	1000BASE-T	0 TO 70	NON-PoE
H5149NL	SINGLE	PCMCIA	3.20	17.78	10.41	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5200NL	DUAL	BGA BUMP GRID ARRAY	11.18	14.73	17.27	1000BASE-T	0 TO 70	4PAIR PoE 30W
H5400NL	QUAD	BGA BUMP GRID ARRAY	11.18	28.45	17.27	1000BASE-T	0 TO 70	4PAIR PoE 30W
H6062NL	SINGLE	SMT	5.72	17.53	16.00	1000BASE-T	0 TO 70	4PAIR PoE 30W
H6080NL	DUAL	SMT	7.24	27.81	15.37	1000BASE-T	0 TO 70	4PAIR PoE 30W
H6096NL	SINGLE	SMT	6.60	18.16	16.00	1000BASE-T	0 TO 70	4PAIR PoE 75W
H6101NL	DUAL	SMT	7.24	27.81	15.37	1000BASE-T	0 TO 70	4PAIR PoE 60W
H6200NL	DUAL	BGA BUMP GRID ARRAY	11.18	14.73	17.27	1000BASE-T	0 TO 70	4PAIR PoE 60W
H6400NL	QUAD	BGA BUMP GRID ARRAY	11.18	28.45	17.27	1000BASE-T	0 TO 70	4PAIR PoE 60W
HX5004ENL	SINGLE	SMT	5.72	17.53	16.00	1000BASE-T	-40 TO +85	NON-PoE
HX5008NL	SINGLE	SMT	6.12	13.16	18.67	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX5014NL	DUAL	SMT	7.24	27.81	15.37	1000BASE-T	-40 TO +85	NON-PoE
HX5020NL	DUAL	SMT	8.33	27.94	10.92	1000BASE-T	-40 TO +85	NON-PoE
HX5062NL	SINGLE	SMT	5.72	17.53	16.00	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX5084NL	SINGLE	SMT	4.00	15.24	10.29	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX5120NL	SINGLE	PCMCIA	2.08	16.51	9.65	1000BASE-T	-40 TO +85	NON-PoE
HX5149NL	SINGLE	PCMCIA	3.20	17.78	10.41	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX5181NL	SINGLE	SMT	6.35	13.84	15.37	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX5200NL	DUAL	BGA BUMP GRID ARRAY	11.18	14.73	17.27	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX5400NL	QUAD	BGA BUMP GRID ARRAY	11.18	28.45	17.27	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX5610NL	SINGLE	BGA BUMP GRID ARRAY	11.18	7.87	17.27	1000BASE-T	-40 TO +85	4PAIR PoE 30W

About Our Ethernet Magnetics

100Base-TX | 1000Base-T | 2.5GBase-T | 5GBase-T | 10GBase-T

1000Base-TX								
MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	PoE RATING
HX6062NL	SINGLE	SMT	5.72	17.53	16.00	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX6080NL	DUAL	SMT	7.24	27.81	15.37	1000BASE-T	-40 TO +85	4PAIR PoE 30W
HX6096NL	SINGLE	SMT	6.60	18.16	16.00	1000BASE-T	-40 TO +85	4PAIR PoE 75W
HX6098NL	SINGLE	SMT	6.60	18.16	16.00	1000BASE-T	-40 TO +85	4PAIR PoE 120W
HX6101NL	DUAL	SMT	7.24	27.81	15.37	1000BASE-T	-40 TO +85	4PAIR PoE 60W
HX6221NL	DUAL	BGA BUMP GRID ARRAY	11.18	14.73	17.27	1000BASE-T	-40 TO +85	4PAIR PoE 60W
HX6400NL	QUAD	BGA BUMP GRID ARRAY	11.18	28.45	17.27	1000BASE-T	-40 TO +85	4PAIR PoE 60W

1000Base-TX - HIGH ISOLATION								
MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	HI-POT RATING
HX5026NL	SINGLE	SMT	6.22max	13.64	14.99	100BASE-TX	-40 TO +85	4.5KVrms
HX5224CNL	SINGLE	SMT	9.65max	12.70	9.65	100BASE-TX	-40 TO +85	4KV * REINFORCED
HXU6200NL	SINGLE	SMT	10.55max	25.40	17.20	100BASE-TX	-40 TO +85	4KV - 2PPP

2.5GBase-T								
MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	PoE RATING
HU4006NL	SINGLE	SMT	5.72	13.72	15.24	2.5GBASE-T	0 TO 70	4PAIR PoE 60W
HU4009NL	SINGLE	SMT	6.60	18.16	16.01	2.5GBASE-T	0 TO 70	4PAIR PoE 60W
HX4019NL	SINGLE	SMT	6.60	18.16	16.01	2.5GBASE-T	-40 TO +85	3KV PoE 60W
HU4102NL	DUAL	SMT	8.33	27.94	10.92	2.5GBASE-T	0 TO 70	NON-PoE
HU4103NL	DUAL	SMT	8.33	27.94	10.92	2.5GBASE-T	0 TO 70	4PAIR PoE 60W
HU4108NL	SINGLE	SMT	8.63	15.24	10.93	2.5GBASE-T	0 TO 70	4PAIR PoE 60W

5GBase-T								
MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	PoE RATING
H5G1002NL	SINGLE	SMT	6.60	18.16	16.01	5GBASE-T	0 TO 70	4PAIR PoE 60W
HX5G1010NL	PCMCIA	SMT	2.08	16.51	9.65	5GBASE-T	-40 TO +85	4PAIR PoE 60W
HX5G2003NL	DUAL	SMT	7.25	27.81	15.37	5GBASE-T	-40 TO +85	4PAIR PoE 60W

10GBase-T								
MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	PoE RATING
H7008FNL	SINGLE	SMT	5.72	13.72	15.24	10GBASE-T	0 TO 70	NON-PoE
H7018FNL	SINGLE	SMT	5.72	13.72	15.24	10GBASE-T	0 TO 70	4PAIR PoE 30W
H7019FNL	SINGLE	SMT	5.72	13.72	15.24	10GBASE-T	0 TO 70	4PAIR PoE 30W
H7028FNL	SINGLE	SMT	5.72	13.72	15.24	10GBASE-T	0 TO 70	4PAIR PoE 60W
H7029FNL	SINGLE	SMT	5.72	13.72	15.24	10GBASE-T	0 TO 70	4PAIR PoE 60W
H7137FNL	SINGLE	SMT	7.24	17.73	15.24	10GBASE-T	0 TO 70	NON-PoE
H7229FNL	SINGLE	SMT	6.35	13.84	15.24	10GBASE-T	0 TO 70	4PAIR PoE 60W
H7232FNL	SINGLE	SMT	8.26	17.73	16.26	10GBASE-T	0 TO 70	4PAIR PoE 140W
H7800NL	SINGLE	SMT	2.54 max	19.40	14.73	10GBASE-T	0 TO 70	NON-PoE
HX7028NL	SINGLE	SMT	5.72	13.72	15.24	10GBASE-T	-40 TO +85	NON-PoE
HX7260NL	SINGLE	SMT	7.87	17.73	16.26	10GBASE-T	-40 TO +85	4PAIR PoE 100W
HX7137NL	SINGLE	SMT	7.24	17.73	15.24	10GBASE-T	-40 TO +85	NON-PoE

HDBaseT Transformers



Pulse HDBaseT transformers are designed to provide common mode noise reduction for improved EMI performance and support power over HDBaseT (PoH) applications of up to 140W. The HDBaseT technology enables 5Play feature set, which includes ultra high definition 4K video, audio, 100BASE-TX Ethernet, various control signals, and up to 100W of power, on a single 100m/328ft CAT5e/6 cable.

Features and Benefits:

- Qualified for Valens chipsets
- Supports Power Over HDBaseT up to 140W
- Suitable for a variety of HDBaseT applications
- High volume production
- Industry standard footprint

HDBaseT Applications

- Blu-ray, DVD, Recorders
- Displays
- Digital Set Top Box
- PC's Projectors
- A/V Receivers
- Game Consoles
- HDMI repeaters, Splitters, Switches

HDBase-T								
MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	PoE RATING
HD8004FNL	SINGLE	SMT	5.72	13.72	15.24	HDBASE-T	0 TO 70	4PAIR PoE 60W
HD8005FNL	SINGLE	SMT	5.72	13.72	15.24	HDBASE-T	0 TO 70	4PAIRPoE 100W
HD8006FNL	SINGLE	SMT	7.87	17.73	16.26	HDBASE-T	0 TO 70	4PAIR PoE 140W
HD8008NL	SINGLE	SMT	5.72	13.72	15.24	HDBASE-T	0 TO 70	4PAIR PoE 30W
HDX8004NL	SINGLE	SMT	5.72	13.72	15.24	HDBASE-T	-40 TO +85	4PAIR PoE 60W
HDX8005NL	SINGLE	SMT	5.72	13.72	15.24	HDBASE-T	-40 TO +85	4PAIR PoE 100W
HDX8006NL	SINGLE	SMT	6.60	18.16	16.00	HDBASE-T	-40 TO +85	4PAIR PoE 140W
HDX8008NL	SINGLE	SMT	5.72	13.72	15.24	HDBASE-T	-40 TO +85	4PAIR PoE 60W

Power Line Communications Transformers

Pulse's Power Line Communications (PLC) transformers are designed to provide safety isolation between the Data TX/RX channels and the High Voltage and Transience associated with mains or power lines.

Features and Benefits:

- Various turns ratio for leading PLC chipsets (Qualcomm, Echelon, STMicro, TI)
- Supports wide bandwidth 3 - 30MHz
- Designed with UL/EN Safety compliance
- Automotive AEC-Q200 options available
- SMT for High Volume production

PLC Applications

- Energy Metering
- Battery Management
- Remote Control/Monitoring
- Smart Grid Management
- Home Ethernet extensions

PLC TRANSFORMERS								
MATERIAL	TURNS RATIO TX/RX:LINE	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	ISOLATION	TEMPERATURE	SAFETY RATING
BX6150NL	1/2CT:1	SMT	6.45	13.38	15.00	3KVrms	-40 TO +85	Supplementary
BX6151NL	1/1:1	SMT	7.62	10.30	14.00	3KVrms	-40 TO +85	Supplementary
BX6152NL	1/1:2	SMT	7.62	10.30	14.00	3KVrms	-40 TO +85	Reinforced
BX6153NL	1:1	SMT	7.62	10.30	14.00	6KVrms	-40 TO +85	Reinforced
BMU6201NL*	1/1:1	SMT	3.94max	5.03	8.13	500Vdc	-40 TO +85	Functional
BM6154NL*	1/1:1	SMT	10.00	9.50	12.00	3KVrms	-40 TO +85	Reinforced
BM6155NL*	1/1:1	SMT	10.00	9.50	12.00	3KVrms	-40 TO +85	Reinforced

* denotes parts are AEC-Q200 approved for Automotive use


About Our BMS Transformers

In large battery pack applications with daisy chain connections, the number of cells connected in series is very high, and the large voltage differences demand component-to-component isolation. The serial communication links between boards need to be isolated by transformer coupling circuits instead of capacitor coupling.

Pulse Electronics Networking BU offers a full line of isolation transformers, and common mode chokes for small to large battery pack systems for serial port safety isolation and EMI noise suppression.

We help designers create battery management systems for higher energy-efficiency modern cars such as EVs, HEVs, and PHEVs. All our battery management parts meet AEC-Q200 requirements for automotive applications.

Our team created the BMS transformers to meet the standards of sophisticated BMS systems. We designed isolation transformers, and common mode chokes to isolate multiple high-energy cells to increase safety and function.



BMS Isolation transformers and common mode chokes

Key Features and Benefits:

- ✔ Supports BMS safety isolation and EMI noise suppression
- ✔ Supports serial Daisy Chain isoSPI, SPI and other signal isolation
- ✔ Meets AEC-Q200 requirements for automotive application
- ✔ Operating temperature: -40°C to +125°C
- ✔ Multiple options for working voltages and voltage isolation
- ✔ Functional, Basic, and reinforced insulation available.

Applications:

- ✔ Electric Vehicle
- ✔ Energy Storage Systems
- ✔ Data Center UPS
- ✔ Solar energy storage
- ✔ Green - Renewable
- ✔ Marine


SMT BMS Parts

MATERIAL	NUMBER OF CHANNELS	ISOLATION VOLTAGE	SCHEMATIC	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	TEMPERATURE	WORKING VOLTAGE	INSULATION
HM1236NL	1	3200 VDC	CMC + XFMR	4.06max	8.64	10.92	-40 TO +125	600	FUNCTIONAL
HM1237NL	2	2500 VRMS	XFMR + CMC	5.72max	11.56	9.53	-40 TO +125	600	FUNCTIONAL
HM1238NL	1	4300 VDC	CMC + XFMR	4.25	8.38	10.50	-40 TO +150	1000	FUNCTIONAL
HM2100NL	2	4300 VDC	XFMR + CMC	3.45max	14.70	14.93	-40 TO +125	1000	FUNCTIONAL
HM2101NL	1	4300 VDC	XFMR + CMC	5.72max	7.62	9.27	-40 TO +125	1000	FUNCTIONAL
HM2102NL	2	4300 VDC	XFMR + CMC	5.00max	14.81	14.73	-40 TO +125	1600	FUNCTIONAL
HM2103NL	1	4300 VDC	XFMR + CMC	5.72max	7.62	9.27	-40 TO +125	1000	FUNCTIONAL
HM2106NL	1	4300 VDC	XFMR	5.75max	8.50	16.84	-40 TO +125	1000	BASIC
HM2108NL	1	4300 VDC	XFMR + CMC	5.75max	8.50	16.84	-40 TO +125	1000	BASIC
HM2112ZNL	2	4300 VDC	XFMR + CMC	3.45max	14.70	15.43	-40 TO +125	1000	FUNCTIONAL
HM2113ZNL	1	4300 VDC	XFMR + CMC	3.45max	9.00	15.43	-40 TO +125	1000	FUNCTIONAL
HM2115ZNL	2	4300 VDC	XFMR + CMC	5.00max	14.95	27.85	-40 TO +85	1000	REINFORCED
HMU1228NL	1	4300 VDC	XFMR	6.85max	8.89	10.03	-40 TO +125	1000	REINFORCED
HMU1228NL	1	4300 VDC	XFMR	6.85max	8.89	10.03	-40 TO +125	1000	BASIC
HM2145NL	2	6220 VDC	XFMR	5.00max	14.95	27.85	-40 TO +125	1000	REINFORCED
HM2147NL	1	4300 VDC	XFMR	3.45max	9.00	15.43	-40 TO +125	1000	BASIC


Automotive Communications

Pulse Electronics 100Base-T1 Automotive | Ethernet Common Mode Choke

Pulse releases the AE2002 100Base-T1 common mode choke for automotive Ethernet applications. In addition to the 100Base-T1 Pulse is in process of releasing the 1000Base-T1 AE5002 and the 100Base-T1 Power over Data Lines (PoDL) AE3003/AE3005/AE3006. Pulse's parts are designed to operate from -40C up to +125C, have high reliability, high volume manufacturing, long term manufacturing support, and meet AEC-Q200 requirements.



AE-Series CMC



HM-Series Ethernet Transformers

Features and Benefits:

- Designed to meet IEEE 802.3bw
- ⊕ Qualified at Marvell, Broadcom, Intel
- ⊕ Meets AEC-Q200 requirements
- ⊕ IATF 16949:2016 certification for 100Base-T1, 1000Base-T1, and PoDL parts in-process
- ⊕ Operating Temp. from -40°C up to +125°C
- ⊕ PPAP Capable

Applications:

- ⊕ Infotainment
- ⊕ Advanced Driver Assist Systems(ADAS) Body Control
- ⊕ Camera/Radar
- ⊕ Gateways
- ⊕ Backbone Diagnostics

AE Auto Chokes

MATERIAL	NUMBER OF PORTS	PACKAGE	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	ISOLATION	TEMPERATURE	PoDL RATING
AE2002	SINGLE	SMT	2.8	4.5	3.2	100BASE-T1	-40 TO +125	NON-PoDL
AE5002	SINGLE	SMT	2.8	4.5	3.2	100BASE-T1	-40 TO +125	NON-PoDL

HM Series Automotive Grade Ethernet

MATERIAL	NUMBER OF PORTS	TURN RATIO	PACKAGE HEIGHT (mm)	PACKAGE LENGTH (mm)	PACKAGE WIDTH (mm)	SPEED	TEMPERATURE	PoE / Hi-POT RATING
HM0068BNL	SINGLE	1CT:1CT / 1CT:1CT	2.40max	12.7	9.65	100BASE-TX	-40 TO +105	NO / 1500Vrms
HM1188NL	SINGLE	1CT:1CT / 1CT:1CT	6.10max	12.7	9.40	100BASE-TX	-40 TO +105	NO / 1500Vrms
HM1193NL	HALF	1CT:1CT	6.10max	12.7	9.40	100BASE-TX	-40 TO +105	NO / 2500Vrms
HM1225NL	SINGLE	1CT:1CT / 1.5CT:1CT	6.10max	12.7	9.40	MOST	-40 TO +95	NO / 1650Vrms
HM1240NL	SINGLE	1CT:1CT / 1.5CT:1CT	6.10max	12.7	9.40	MOST	-40 TO +95	NO / 1650Vrms
HM5004ENL	SINGLE	(4x) 1CT:1CT	5.97max	17.65	16.00	1000BASE-T	-40 TO +85	NO / 1500Vrms
HM5149NL	SINGLE	(4x) 1CT:1CT	3.20max	17.78	10.41	1000BASE-T	-40 TO +125	NO / 1500Vrms
HM5165NL	SINGLE	(4x) 1CT:1CT	5.97max	17.65	16.00	1000BASE-T	-40 TO +125	30W / 1500Vrms
HM6098NL	SINGLE	(4x) 1CT:1CT	6.85max	18.16	16.00	1000BASE-T	-40 TO +105	130W / 1500Vrms
HM2130NL	SINGLE	(4x) 1CT:1CT	8.10max	20.00	9.40	Multi-Gig B-T	-40 TO +155	NO / 500V
HM7142NL	SINGLE	(4x) 1CT:1CT	5.97max	17.78	10.41	10GBASE-T	-40 TO +125	30W / 1500Vrms



Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2020. Pulse Electronics, Inc. All rights reserved.

For More Information, Visit us online at PulseElectronics.com