

POWER INDUCTORS

HIGH CURRENT COMPOSITE CORE









POWER INDUCTORS

HIGH CURRENT COMPOSITE CORE INDUCTORS

Our composite core inductors come in multiple platform sizes and provide a fully shielded, high energy storage, soft saturation solution for applications up to 120Apk current. The construction enables the highest energy density of any available SMT inductor and also minimizes acoustic noise. With both commercial grade (-40C to 125C) and automotive grade (-55C to 155C) offerings they cover a wide range of applications and markets including Datacom, Computing, Industrial and Automotive.







FEATURES & BENEFITS

- Low Profile, High Current Applications
- Composite core material for higher energy storage density
- Lowest DCR/mm3
- Soft saturation characteristics
- Larger terminations for lower DCR and stronger solder joint
- Computing, Communications, Industrial and Automotive Applications
- Excellent temperature stability
- Handles high transient current spikes without saturation
- Suitable for High Frequency Applications

POWER INDUCTORS

HIGH CURRENT COMPOSIT CORE INDUCTORS







Part Number	Industry Size Code	Dimensions (mm Max)										Inductance (μH)						
		L	W	Н	_ ا			0.1				1			10			100
PA5001/PM2201	4020	4.3	4.3	2.1	3	3 A	pk					6 Apk						
PA5430/PM5430	4030	4.3	4.3	3.1	П							5.5 Apk	<u> </u>		3.6 Apk			
PA5431/PM5431	4040	4.3	4.3	4.1	Π								4.	0 Apk	,	2.9 Apk		
PA5002/PM2202	5020	5.7	5.7	2.1	Π				27 Apk			11.7 Apk						
PA5003/PM2203	5030	5.7	5.7	3.1	Π		П		32.5 Apk					7 Apk				
PA5175/PM5175	5050	5.7	5.7	5.0	Π								7.2 Ap	k	5.4 Apk			
PA5004/PM2204	6030	6.8	6.6	3.1	Π				36 Apk					8 Apk				
PA5005/PM2205	6050	6.8	6.6	5.0	Π					20Ap	k			6.8 A	k			
PA5432/PM5432	6060	6.8	6.6	6.1	[10.5 Apk						5.6 Apk		
PA5006/PM2206	7020	8.0	7.8	2.1	Π				32 Ap	k		20 Apk						
PA5007/PM2207	7030	8.0	7.8	3.1	Π					28 A	pk				9 Apk			
PA2240/PM2240	7070	8.0	7.8	7.0	Π							15.1 Apk		11	Apk			
PA2241/PM2241	8080	8.6	8.3	8.0	Π							24 Apk			10 Apk			
PA2242/PM2242	1030	11.8	10.5	3.1	ΙΓ				58 Ap	k		25 Apk						
PA2243/PM2243	1060	11.8	10.5	6.0	Π					50 Apk				22 A	k			
PA2244/PM2244	1010	11.8	10.5	10.0	[50 A	pk					15.5 Apk		
PA5433/PM5433	1580	16.8	15.8	8.0								52 Apk				16 Apk		
PA2247/PM2247	1510	16.8	15.8	10.0	Π		П					39 /	Apk				16.7 Apk	
PA2248/PM2248	1513	16.8	15.8	13.0	1 [П	44 /	Apk		1		19 Apk	

Other Great Products from Pulse Electronics



Power Inductors

- Power Bead, Molded, Composite, Drum Core and Toroid Constructions
- Over 100Apk



Switch Mode Transformers

- Multiple Topologies
- Up to 2kW
- Functional, Basic and Reinforced Insulation



Isolation Transformers

- Push-pull, Flyback and H-Bridge topologies
- Functional, Basic and Reinforced Insulation
- Up to 5kVrms Hi-pot*



Common Mode Chokes

- NiZn, MnZn and Nanocrystaline Materials
- Up to 45Arms



Current Sense Magnetics

- Functional, Basic and Reinforced Insulation
- Up to 40Arms